C EUROPEAN PATENT OFICE

	_			
Patent Abstra	cts of Japan		(a)	2
PUBLICATION N PUBLICATION D		: 2001076886 : 23-03-01	(b) (c)	2
APPLICATION D		: 03-09-99 : 11250181	(d)	5b 5a 3
	FUTABA CORP;		(e)	2
	OGAWA YUKIO; H05B 33/28 H01 H01H 13/52 H05	1H 11/00 H01H 13/02 5B 33/10 H05B 33/14	(1)	\$ 50 50 3 3 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5
TITLE :	ORGANIC EL DE TRANSPARENT ITS MANUFACT	TOUCH SWITCH AND) (g)	8 11a 11b 12 6 5 6 6 5 8 6
			(h)	

ABSTRACT: PROBLEM TO BE SOLVED: To offer simpler construction than conventional, permitting inexpensive manufacture, and restrict the lowering of brightness due to interference light.

> SOLUTION: After a cathode 3 formed with a metal electrode is formed on an insulating substrate 2 and then an organic insulating layer 4 is formed on the cathode 3 so as to partition a luminescent portion 7. Followingly, an organic layer 5 is formed on the insulating layer 4 and a transparent anode 6 is formed on the organic layer 5. On the other hand, a switching electrode 12 is formed on a transparent base material 11 to electrically form a matrix with the anode 6 and a elastic spacer 14 is formed between the base material 11 and the switching electrode 12. The substrate 2 is sealed to the base material 11 to form a transparent touch switch 13 with the anode 6 and the switching electrode 12. An organic EL device 1 is thus manufactured.

COPYRIGHT: (C)2001, JPO